## AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

- (Currently Amended) A process for preparing a controlled release tablet of potassium chloride comprising:
  - (a) microencapsulating potassium chloride crystals with an inner membrane of comprising ethylcellulose by coacervation or phase separation to form potassium chloride microcapsules;
  - (b) coating said potassium chloride microcapsules with an outer membrane comprising a plasticized polymer to form compressible coated microcapsules;
  - (c) preparing a compressible blend comprising said compressible coated microcapsules, microcrystalline cellulose, a disintegrant and colloidal silicon dioxide; and
    (d) compressing said compressible blend into tablets,

wherein the tablet hardness is at least about 14 kP, the friability of the tablets does not exceed about 0.3%, the tablet rapidly disperses into granules on contact with water and the tablets exhibits a dissolution profile substantially corresponding to the following pattern when tested by USP Apparatus 2 (Paddles @ 50 rpm) in purified water:

after 2 hours, about 30% to about 50% of the total potassium chloride is released; after 4 hours, about 60% to about 75% of the total potassium chloride is released; and after 8 hours, not less than 80% of the total potassium chloride is released.

- (Currently Amended) The process of claim 1, wherein said <u>compressible blend further</u> <u>comprises a</u> disintegrant is selected from the group consisting of sodium starch glycolate, <u>Crosearmellose sodium</u>, cross linked polyvinylpyrrolidone, and combinations thereof.
- 3. (Previously Presented) The process of claim 2 wherein said disintegrant is present in an amount of from about 0.5% to about 5.0% by weight based on the tablet weight.
- 4. (Previously Presented) The process of claim 1 wherein said plasticized polymer comprises a

- 5. (Previously Presented) The process of claim 4 wherein said plasticized polymer comprises ethylcellulose and said coating step comprises coating said potassium chloride microcapsules with an aqueous dispersion of ethylcellulose.
- (Original) The process of claim 5 wherein said plasticized polymer comprises ethylcellulose and diethyl phthalate.
- (Previously Presented) The process of claim 1 wherein said microcrystalline cellulose comprises not more than about 15% by weight of said tablet.
- 8. (Currently Amended) The process of claim 1 wherein the inner membrane-of-ethyleellulose comprises-an ethylcellulose having a viscosity between about 90 cps and about 110 cps.
- 9. (Original) The process of claim 8 wherein said ethylcellulose forming the inner membrane comprises between about 8% and about 20% by weight of said potassium chloride microcapsules.
- 10. (Previously Presented) The process of claim 1 wherein said colloidal silicon dioxide is present in an amount of from about 0.1% to about 0.3% by weight of said tablet.
- 11. (Original) The process of claim 3 wherein said compressible blend further comprises from about 0.1% to about 1.0% of a surfactant based on the weight of said tablet.
- 12. (Original) The process of claim 1 wherein said plasticized polymer comprises a plasticizer selected from the group consisting of dibutyl sebacate, diethyl phthalate, triacetin, triethyl citrate, polyethylene glycols of different molecular weights and mixtures thereof.

- 13. (Original) The process of claim 12 wherein said plasticizer comprises from about 2% to 40% based on the weight of the plasticized polymer.
- 14. (Original) The process of claim 1 wherein said outer membrane coating comprises from about 0.5% to about 5.0% by weight of said compressible coated microcapsules.
- 15. (Previously Presented) The process of claim 1 wherein said plasticized polymer comprises hydroxypropyl methylcellulose and polyethylene glycol 400.
- 16. (Original) The process of claim 1 wherein said compressible blend is substantially free of lubricants.
- 17. (Currently Amended) The process of claim 1 wherein said plasticized polymer comprises ethylcellulose and diethyl phthalate, and said outer membrane compressible coated microcapsules comprises from about 0.5% to about 5% by weight of said compressible coated microcapsules outer membrane, and said compressible blend comprises about 0.1% to 0.2% by weight colloidal silicon dioxide and not more than about 15% by-5 weight of said microcrystalline cellulose.
- 18. (Currently Amended) The process of claim 17, wherein-said compressible blend further comprising a disintegrant is-present in an amount of from about 0.5% to about 3% by weight of said compressible blend.
- 19. (Original) A controlled release potassium chloride tablet prepared by the process of claim 1.

_	plasticized		
а	piasucizeu	po.	LY IIICI

- b) colloidal silicone dioxide; and
- c) microcrystalline cellulose,

wherein the tablet hardness is at least about 14 kP, the friability of the tablets does not exceed about 0.3%, the tablet rapidly disperses into granules on contact with water-and the tablets exhibits a dissolution profile substantially corresponding to the following pattern when tested by USP Apparatus 2 (Paddles @ 50 rpm) in purified water:

after 2 hours, about 30% to about 50% of the total potassium chloride is released.

after 4 hours, about 60% to about 75% of the total potassium chloride is released; and

after 8 hours, not less than 80% of the total potassium chloride is released.

- 21. (Previously Presented) The controlled release potassium chloride tablet of claim 20 wherein said inner membrane comprises between about 8% and about 20% by weight of said microcapsules.
- 22. (Previously Presented) The controlled release potassium chloride tablet of claim 20 wherein said plasticized polymer comprises a polymer selected from the group consisting of ethyl cellulose, polyvinylpyrrolidone and hydroxypropylmethylcellulose.
- 23. (Currently Amended) The controlled release potassium chloride tablet of claim 21 wherein said outer membrane coating microcapsules comprises from about 0.5% to about 5.0% by weight of said compressible coated microcapsulesouter membrane.
- 24. (Original) The controlled release potassium chloride tablet of claim 20 wherein said tablet further comprises a disintegrant.
- 25. (Currently Amended) The controlled release potassium chloride tablet of claim 24 wherein said disintegrant eomprises is selected from the group consisting of sodium starch glycolate,

croscarmellose sodium, cross-linked polyvinylpyrrolidone.

- 26. (Original) The controlled release potassium chloride tablet of claim 20 wherein the potassium chloride is present in an amount effective for the treatment of potassium deficiency in humans by oral administration.
- 27. (Original) The controlled release potassium chloride tablet of claim 20 wherein said tablet is substantially free of lubricants.
- 28. (Original) The controlled release potassium chloride tablet of claim 20 wherein said plasticized polymer comprises ethyl cellulose and diethyl phthalate.
- 29. (Currently Amended) A method of treating potassium deficiency in <u>a</u> subjects in need of potassium, comprising administering to the subject an effective amount of the controlled release potassium chloride tablet of claim 20.
- 30. (Previously Presented) The controlled release potassium chloride tablet of claim 20, wherein said colloidal silicon dioxide is present in an amount of from about 0.1% to about 0.3% by weight of the total tablet weight.
- 31. (Currently Amended) The controlled release potassium chloride tablet of claim 20, wherein said microcrystalline cellulose is present in an amount of not more than about 15% by weight of the total tablet weight.
- 32. (New) The process of claim 2, wherein said disintegrant is selected from the group consisting of sodium glycolate, croscarmellose sodium, cross-linked polyvinylpyrrolidone, and combinations thereof.
- 33. (New) The controlled release potassium chloride tablet of claim 20, further comprising a disintegrant and optionally a surfactant, wherein said tablet is substantially free of lubricants.

- 34. (New) The controlled release potassium chloride tablet of claim 20, wherein said plasticized polymer comprises a plasticizer selected from the group consisting of dibutyl sebacate, diethyl phthalate, triacetin, triethyl citrate, polyethylene glycols of different molecular weights, and mixtures thereof.
- 35. (New) The controlled release potassium chloride tablet of claim 20, wherein said plasticized polymer comprises from about 2% to 40% of the plasticizer.